

Endraft® Air Conditioner Cover

Thank you for participating in National Grid's Savings Your Way Program. Enclosed is your Endraft® air conditioner cover to reduce energy loss in the off-season when your AC unit is not in use. These instructions will help guide you through the cover's installation process.

Your package contains:

- Endraft® air conditioner cover
- Wind-block insulating liner
- Roll of removeable tape for installation

To install your cover, you will need:

- A tape measure or ruler
- Scissors

Directions to install your cover:

Step 1

Unplug the air conditioner's electric cord and wrap it tightly around the unit as close as possible to the front edge. Secure the wrapped cord with a 3" piece of tape.

Step 2

Prepare to cut the wind-block liner by first measuring the height and width of the AC unit. Add 6" to the height of the liner then add 6" to the width. Cut the wind-block liner to size with scissors.



Step 3

Center the wind-block liner over the front of the unit, overlapping 3" on all sides. Fold and tape square corners then tape the entire edge of the wind-block liner to the unit. Be sure to overlap the tape so half is affixed to the wind-block liner and half is affixed to the AC unit. For best results, make sure that the wind-block liner covers the electric cord, plug, and the opening where the electric cord exits the AC unit.

Note: Tape adheres best when outside temperature is above 35° F.

Step 4

Place the Endraft cover over the air conditioner.

That's it! Your Endraft cover is installed and ready to protect against air leaks and energy loss.